

Proven Preventative Maintenance

MIDTRONICS

EXP-800

Battery and Electrical Diagnostic Analyzer with Integrated Printer

Building on advanced EXP technology with additional program management features, the Midtronics EXP-800 sets the standard for professional battery and electrical preventative maintenance. Features like easy-to-use controls, compact size, and an integrated printer, make the EXP-800 the ideal choice for any service shop looking to make preventative maintenance part of their value-added solutions.

Features:

New Dynamic Conductance Battery Testing Technology

- Combines direct temperature measurement with deep scan technology to improve accuracy and decisiveness
- Advanced preventative maintenance algorithms for identifying batteries as they approach end-of-life

Advanced Electrical System Diagnostics Featuring Digital Signal Processing

- Digital Signal Processing (DSP) creates a digitized picture of the measured alternator output voltage to analyze the amplitude level and frequency of the diode ripple pattern for improved accuracy and identification of open or shorted diodes and open phase conditions, (multiple diode failure or winding problems)

Advanced Communications Capabilities

- Integrated printer to enhance and enforce the selling/service process
- Integrated data card read/write drive for simple software update capability and data storage

Superior User Interface

- Large graphical screen for icons and improved explanations
- Scroll bar capability means fewer overall screens
- Hot keys improve logic and flow



INNOVATION



TECHNOLOGY



QUALITY



WORLDWIDE

NASCAR Performance® is a registered trademark of the National Association of Stock Car Auto Racing, Inc.

EXP-800

Battery and Electrical Diagnostic Analyzer with Integrated Printer

Specifications:

Model:

- EXP-800
Battery and electrical diagnostic analyzer with integrated printer

Applications:

- 6 and 12 volt batteries
- 12 and 24 volt charging system

Power Requirements:

- (6) AA Alkaline batteries

Battery Applications:

- Automotive
- Marine battery
- Motorcycle
- Group 31
- Commercial—4D/8D
- Lawn and Garden

Battery Chemistries:

- Regular (flooded)
- AGM Spiral
- AGM
- Gel

Rating System	Range
CCA	100 – 3000
CA	100 - 3000
MCA	100 - 3000
JIS	By JIS number
DIN	100 – 1000
SAE	100 – 3000
IEC	100 – 1000
EN	100 – 3000

DC Voltage

0 - 60 V, 0.05% +/- .03 VDC

Measured Temperature

-20 to 200° F 1.0% +/- 5°
(-28.8 to 93.3° C)

Display:

- 128 x 64 pixel graphic, backlit display

Operating Temperature:

- 32° F – 120° F (0° C – 49° C)

Test Leads:

- 4 ft cable with HD dual conductor Kelvin clamps

Housing Material:

- ABS plastic

Dimensions:

- 9 ½ in H x 4 in W x 2 ½ in D

Weight:

- 1 lb / 427 g

Soft-Sided Carrying Case/Toolbag

Languages:

- English
- French-Canadian
- Spanish




EXP-800 KIT

EXP800

WILLS CAR CATILLE
1060 W. ADDISON S
CHICAGO, IL
60610
800 867-5309
WWW.CATILLE.COM

10/19/2007
2:32 PM



NO START TEMP: 10°F

BATTERY MAY NOT START
VEHICLE AT OR BELOW
THIS TEMPERATURE OR
IN EXTREME CONDITIONS

BATTERY AGE: 81 MO.
AVERAGE BATTERY LIFE
IN THIS AREA 59 MO

BATTERY IS
APPROACHING THE END
OF ITS USEFUL LIFE.

SUGGEST REPLACEMENT

Sample Printout

Corporate Headquarters

Willowbrook, IL USA
USA Toll Free: 1.800.776.1995
Phone: 1.630.323.2800
Fax: 1.630.323.2844
E-Mail: net2@midtronics.com

Canadian Inquiries

Toll Free: 1.866.592.8053
Fax: 1.630.323.7752
E-Mail: canada@midtronics.com

Midtronics b.v.

European Headquarters
Serving Europe, Africa, the Middle
East, and The Netherlands
Phone: +31 306 868 150
Fax: +31 306 868 158
E-Mail: info-europe@midtronics.com

European Sales Locations

IJsselstein, The Netherlands
Paris, France
Dusseldorf, Germany

Midtronics China Office

China Operations
Shenzhen, China
Phone: +86 755 8202 2037
Fax: +86 755 8202 2039
E-Mail: chinainfo@midtronics.com
Asia/Pacific (excluding China)
Contact Corporate Headquarters at
+1.630.323.2800 or
E-Mail: asiapacinfo@midtronics.com